



Circuit breaker size S0 for motor protection, CLASS 10 A-release 7...10 A  
N release 130 A screw terminal Standard switching capacity

|                                                                                     |                      |
|-------------------------------------------------------------------------------------|----------------------|
| product brand name                                                                  | SIRIUS               |
| product designation                                                                 | Circuit breaker      |
| design of the product                                                               | For motor protection |
| product type designation                                                            | 3RV2                 |
| <b>General technical data</b>                                                       |                      |
| size of the circuit-breaker                                                         | S0                   |
| size of contactor can be combined company-specific                                  | S00, S0              |
| product extension auxiliary switch                                                  | Yes                  |
| power loss [W] for rated value of the current                                       |                      |
| • at AC in hot operating state                                                      | 9.25 W               |
| • at AC in hot operating state per pole                                             | 3.1 W                |
| insulation voltage with degree of pollution 3 at AC rated value                     | 690 V                |
| surge voltage resistance rated value                                                | 6 kV                 |
| maximum permissible voltage for safe isolation in networks with grounded star point |                      |
| • between main and auxiliary circuit                                                | 400 V                |
| • between main and auxiliary circuit                                                | 400 V                |
| shock resistance acc. to IEC 60068-2-27                                             | 25g / 11 ms          |
| mechanical service life (switching cycles)                                          |                      |
| • of the main contacts typical                                                      | 100 000              |
| • of auxiliary contacts typical                                                     | 100 000              |
| electrical endurance (switching cycles) typical                                     | 100 000              |
| type of protection according to ATEX directive 2014/34/EU                           | Ex II (2) GD         |
| certificate of suitability according to ATEX directive 2014/34/EU                   | DMT 02 ATEX F 001    |
| reference code acc. to IEC 81346-2                                                  | Q                    |
| <b>Ambient conditions</b>                                                           |                      |
| installation altitude at height above sea level maximum                             | 2 000 m              |
| • ambient temperature during operation                                              | -20 ... +60 °C       |
| • ambient temperature during storage                                                | -50 ... +80 °C       |
| • ambient temperature during transport                                              | -50 ... +80 °C       |
| temperature compensation                                                            | -20 ... +60 °C       |
| relative humidity during operation                                                  | 10 ... 95 %          |
| <b>Main circuit</b>                                                                 |                      |
| number of poles for main current circuit                                            | 3                    |
| adjustable current response value current of the                                    | 7 ... 10 A           |

|                                                                      |                                                                                        |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>current-dependent overload release</b>                            |                                                                                        |
| • operating voltage rated value                                      | 690 V                                                                                  |
| • operating voltage at AC-3 rated value maximum                      | 690 V                                                                                  |
| <b>operating frequency rated value</b>                               | 50 ... 60 Hz                                                                           |
| <b>operational current rated value</b>                               | 10 A                                                                                   |
| operational current at AC-3 at 400 V rated value                     | 10 A                                                                                   |
| operating power at AC-3                                              |                                                                                        |
| • at 230 V rated value                                               | 2 200 W                                                                                |
| • at 400 V rated value                                               | 4 000 W                                                                                |
| • at 500 V rated value                                               | 5 500 W                                                                                |
| • at 690 V rated value                                               | 7 500 W                                                                                |
| operating frequency at AC-3 maximum                                  | 15 1/h                                                                                 |
| <b>Auxiliary circuit</b>                                             |                                                                                        |
| <b>number of NC contacts for auxiliary contacts</b>                  | 0                                                                                      |
| <b>number of NO contacts for auxiliary contacts</b>                  | 0                                                                                      |
| number of CO contacts for auxiliary contacts                         | 0                                                                                      |
| <b>Protective and monitoring functions</b>                           |                                                                                        |
| <b>product function</b>                                              |                                                                                        |
| • ground fault detection                                             | No                                                                                     |
| • phase failure detection                                            | Yes                                                                                    |
| <b>trip class</b>                                                    | CLASS 10                                                                               |
| <b>design of the overload release</b>                                | thermal                                                                                |
| <b>breaking capacity operating short-circuit current (Ics) at AC</b> |                                                                                        |
| • at 240 V rated value                                               | 100 kA                                                                                 |
| • at 400 V rated value                                               | 100 kA                                                                                 |
| • at 500 V rated value                                               | 42 kA                                                                                  |
| • at 690 V rated value                                               | 4 kA                                                                                   |
| <b>breaking capacity maximum short-circuit current (Icu)</b>         |                                                                                        |
| • at AC at 240 V rated value                                         | 100 kA                                                                                 |
| • at AC at 400 V rated value                                         | 100 kA                                                                                 |
| • at AC at 500 V rated value                                         | 42 kA                                                                                  |
| • at AC at 690 V rated value                                         | 6 kA                                                                                   |
| response value current of instantaneous short-circuit trip unit      | 130 A                                                                                  |
| <b>UL/CSA ratings</b>                                                |                                                                                        |
| <b>full-load current (FLA) for 3-phase AC motor</b>                  |                                                                                        |
| • at 480 V rated value                                               | 10 A                                                                                   |
| • at 600 V rated value                                               | 10 A                                                                                   |
| <b>yielded mechanical performance [hp]</b>                           |                                                                                        |
| • for single-phase AC motor                                          |                                                                                        |
| — at 110/120 V rated value                                           | 0.5 hp                                                                                 |
| — at 230 V rated value                                               | 1.5 hp                                                                                 |
| • for 3-phase AC motor                                               |                                                                                        |
| — at 200/208 V rated value                                           | 2 hp                                                                                   |
| — at 220/230 V rated value                                           | 3 hp                                                                                   |
| — at 460/480 V rated value                                           | 5 hp                                                                                   |
| — at 575/600 V rated value                                           | 7.5 hp                                                                                 |
| <b>Short-circuit protection</b>                                      |                                                                                        |
| <b>product function short circuit protection</b>                     | Yes                                                                                    |
| <b>design of the short-circuit trip</b>                              | magnetic                                                                               |
| <b>Installation/ mounting/ dimensions</b>                            |                                                                                        |
| <b>mounting position</b>                                             | any                                                                                    |
| <b>fastening method</b>                                              | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715 |
| <b>height</b>                                                        | 97 mm                                                                                  |
| <b>width</b>                                                         | 45 mm                                                                                  |
| <b>depth</b>                                                         | 97 mm                                                                                  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>for grounded parts at 400 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>at the side</li> </ul> </li> <li>for live parts at 400 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>at the side</li> </ul> </li> <li>for grounded parts at 500 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>at the side</li> </ul> </li> <li>for live parts at 500 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>at the side</li> </ul> </li> <li>for grounded parts at 690 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>backwards</li> <li>at the side</li> <li>forwards</li> </ul> </li> <li>for live parts at 690 V <ul style="list-style-type: none"> <li>downwards</li> <li>upwards</li> <li>backwards</li> <li>at the side</li> <li>forwards</li> </ul> </li> </ul> | 30 mm<br>30 mm<br>9 mm<br><br>30 mm<br>30 mm<br>9 mm<br><br>30 mm<br>30 mm<br>9 mm<br><br>50 mm<br>50 mm<br>0 mm<br>30 mm<br>0 mm<br><br>50 mm<br>50 mm<br>0 mm<br>30 mm<br>0 mm              |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                               |
| product function removable terminal for auxiliary and control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | No                                                                                                                                                                                            |
| <b>type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>for main current circuit</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | screw-type terminals                                                                                                                                                                          |
| <b>arrangement of electrical connectors for main current circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Top and bottom                                                                                                                                                                                |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>for main contacts <ul style="list-style-type: none"> <li>solid or stranded</li> <li>finely stranded with core end processing</li> </ul> </li> <li>at AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2x (1 ... 2,5 mm <sup>2</sup> ), 2x (2,5 ... 10 mm <sup>2</sup> )<br>2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup><br>2x (16 ... 12), 2x (14 ... 8) |
| <ul style="list-style-type: none"> <li>tightening torque for main contacts with screw-type terminals</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2 ... 2.5 N·m                                                                                                                                                                                 |
| <b>design of screwdriver shaft</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Diameter 5 to 6 mm                                                                                                                                                                            |
| <b>size of the screwdriver tip</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Pozidriv 2                                                                                                                                                                                    |
| <b>design of the thread of the connection screw</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>for main contacts</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | M4                                                                                                                                                                                            |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                               |
| <b>B10 value</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>with high demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 5 000                                                                                                                                                                                         |
| <b>proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>with low demand rate acc. to SN 31920</li> <li>with high demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50 %<br>50 %                                                                                                                                                                                  |
| <b>failure rate [FIT]</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>with low demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50 FIT                                                                                                                                                                                        |
| <b>T1 value for proof test interval or service life acc. to IEC 61508</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 10 y                                                                                                                                                                                          |
| <b>protection class IP on the front acc. to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | IP20                                                                                                                                                                                          |
| <b>touch protection on the front acc. to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | finger-safe, for vertical contact from the front                                                                                                                                              |

## Certificates/ approvals

|                          |                                |
|--------------------------|--------------------------------|
| General Product Approval | For use in hazardous locations |
|--------------------------|--------------------------------|



[KC](#)



|                                |                           |                   |                   |
|--------------------------------|---------------------------|-------------------|-------------------|
| For use in hazardous locations | Declaration of Conformity | Test Certificates | Marine / Shipping |
|--------------------------------|---------------------------|-------------------|-------------------|



[Miscellaneous](#)



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



## Marine / Shipping



|       |         |
|-------|---------|
| other | Railway |
|-------|---------|

[Confirmation](#)



[Confirmation](#)

[Vibration and Shock](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2021-1JA10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2021-1JA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2021-1JA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2021-1JA10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2021-1JA10&lang=en)


Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RV2021-1JA10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV2021-1JA10&objecttype=14&gridview=view1>







last modified:

12/15/2020