



Figure similar

*** spare part *** SIMATIC DP, connection ET 200M IM 153-4 PN IO for max. 12 S7-300 modules, extended functions: isochronous real time communication class 1 and 2, module exchange without PG, operation without MMC, maintenance support of new IO modules

General information	
Product type designation	IM 153-4 PN ST
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0302H
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	In a construction with grounded reference potential, a fuse is necessary for redundant interface modules (Recommendation: 2.5 A)
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	600 mA; with 24 V DC supply
Inrush current, typ.	4 A
I ² t	0.09 A ² ·s
output voltage / header	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	6 W
Address area	
Addressing volume	
• Inputs	192 byte
• Outputs	192 byte
Hardware configuration	
number of modules per DP device interface, max.	12
Protocols	
Bus protocol/transmission protocol	PROFINET IO
Protocols (Ethernet)	
• TCP/IP	No
Redundancy mode	
• PROFINET system redundancy (S2)	No
Media redundancy	
— MRP	Yes
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• LINK LED	Yes; green LED

• RX/TX LED	Yes; Yellow LED
• for module diagnostics	Yes
Potential separation	
Potential separation exists	Yes
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Dimensions	
Width	40 mm
Height	125 mm
Depth	118 mm
Weights	
Weight, approx.	215 g
Classifications	

	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[KC](#)



EMV

For use in hazardous locations



[FM](#)



For use in hazardous locations

Marine / Shipping



[Miscellaneous](#)

[CCC-Ex](#)



Marine / Shipping

Industrial Commu-



[NK / Nippon Kaiji Ky-](#)
[okai](#)



[CCS \(China Classifica-](#)
[tion Society\)](#)

[PROFINET](#)

last modified:

12/8/2024